

Street Sign Basics

- There shall be no punctuation or unapproved designations included in the street signs.
- Cross blades are required at all intersecting streets and signs shall be positioned so that the blades are parallel to the corresponding street.
- Temporary street signs are to be installed prior to approving any building permits and permanent street signs are required prior to issuing a certificate of occupancy.
- An inspection of all installed street signs is required. Signs shall reflect the street name and designations approved by the Addressing Office, as noted through Development Review project comments. Contact Addressing after signs are installed for inspection (email: addressing@seminolecountyfl.gov).
- For Street Sign requirements please contact the Seminole County Traffic Engineering Division at 407-665-5677
- Below are examples of designations to be abbreviated per MUTC Section 2E.17.

• Avenue	AVE	Parkway	PKWY
• Boulevard	BLVD	Pass	PASS
• Causeway	CSWY	Place	PL
• Circle	CIR	Point	PT
• Court	CT	Road	RD
• County Road	CR	Run	RUN
• Cove	CV	State Road	SR
• Drive	DR	Street	ST
• Highway	HWY	Terrace	TER
• Lane	LN	Trail	TRL
• Loop	LOOP	Way	WAY

Temporary Street Sign Standards (required prior to permit approval)

Aids responding emergency personnel in locating work sites more effectively and to standardize the appearance of temporary street signs at construction sites in Seminole County.

- Temporary street signs shall be in place and inspected by the Addressing Office prior to approval of any building permits (It is the Contractor/Developer's responsibility to periodically inspect that signs are still in place and legible. Failure to maintain street signs could result in a Notice of Code Violation).
- All letters shall be 4 inches in height and at least 1 inch line width, shall be black in color and contrast with the immediate white background.
- Street signs shall be securely mounted with a minimum height of 6 foot.



Permanent Street Sign Standards (required prior to Certificate of Occupancy)

Overhead Illuminated Street ID Specs:

White legend and border. Material is white translucent Lexan with Translucent Green 3M 1177 EC film background or for retroreflective panel use clear Lexan sheeted with 3M DG3 4090T sheeting with Translucent Green 3M 1177 EC film background. Border and radius will vary based on type of street id body used. Font is Highway Gothic upper and lower case with a minimum of 8 inch upper / 6 inch lower case letters. Length and width varies with street name or names.



Overhead Aluminum ID Specs:

White DG3 legend and border with Translucent Green 3M 1177 EC film background, Font is Highway Gothic upper and lower case with a minimum of 8 inch upper / 6 inch lower case letters. Border is 1 inch with 1.5 inch radius. Length and width varies with street name or names.



Ground Mount:

White HIP or better legend and border with Translucent Green 3M 1177 EC film background. Font is Highway Gothic (B) or (C) upper and lower case with a minimum of 6 inch upper / 4.5 inch lower case letters. Border is .5 inch with 1 inch radius. Standard sizes of 24 in x 9 in / 30 in x 9 in / 36 in x 9 in and 42 in x 9 in. Any length over 42 inch is used only if necessary. Blades will be mounted to both sides of a twist bracket, which is then mounted inside the u-channel, behind stop sign. The Seminole County logo is used only at County maintained roads and is 5 inch x 3inch, centered vertically and should be positioned to the left of the street name. No logo or empty space for private roads.

